

Datum: 30.04.2025



(slika je simbolična)

## Visokotlačni reg. 60 barG 3/8Regulacijsko območje 0.5 - 12 bar

Kategorija: [High pressure regulators up to 60 bar](#)

Šifra: **101147RIE**

### Kratek opis

High pressure regulator 60 bar, G 3/8, Control range 0.5 - 12 bar, Input pressure max. 60 bar, Operating temp. -10 °C to 90 °C

Reversible piston-type pressure regulator, virtually independent of inlet pressure, with self-relieving design, manufactured entirely in brass.

Specially designed for high pressures up to 60 bar. Pressure catch with counter nut.

### Tehnične Specifikacije

|                               |                                                                                                                                 |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Min. delovna temperatura [°C] | -10                                                                                                                             |
| Aplikacije                    | Compressed air and other neutral, non-flammable gases<br>At $P_1 = 20$ bar, $P_2 = 10$ bar and pressure drop $\Delta p = 4$ bar |
| Merjenje pretoka              |                                                                                                                                 |
| Navoj                         | G 3/8                                                                                                                           |
| Ohišje                        | Brass                                                                                                                           |
| Tesnilo                       | NBR                                                                                                                             |
| Min. krmilno območje [bar]    | 0.5                                                                                                                             |
| Max. krmilno območje [bar]    | 12                                                                                                                              |
| C [mm]                        | 31.0                                                                                                                            |
| Max. vhodni tlak [bar]        | 60                                                                                                                              |
| A [mm]                        | 72.0                                                                                                                            |
| Max. delovna temperatura [°C] | 90                                                                                                                              |
| D [mm]                        | 133.0                                                                                                                           |
| B [mm]                        | 164.0                                                                                                                           |
| Pretok [l/min]                | 2500                                                                                                                            |