

Datum: 29.04.2025



(slika je simbolična)

## Vklopni ventil »multifix« z nastavljivim gumbom Vel. 5G 3/4

Kategorija: [Start-up valves](#)

Šifra: **100628RIE**

### Kratek opis

Start up valve »multifix«, with adjustable throttle, Size 5, G 3/4, Input pressure 2 - 16 bar, Medium / ambient temp. max. 60 °C

Seat valves operated by secondary pressure for controlled pressurisation of pneumatic systems.

The full cross-section of the regulator is opened at 50% of the input pressure.

The filling time can be altered by turning the adjusting screw.

### Tehnične Specifikacije

|                              |                                                       |
|------------------------------|-------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 3/4                                                 |
| Ohišje                       | Aluminium                                             |
| Serija                       | multifix                                              |
| Tesnilo                      | NBR                                                   |
| Min. vhodni tlak [bar]       | 2                                                     |
| Velikost                     | 5                                                     |
| Max. vhodni tlak [bar]       | 16                                                    |
| D [mm]                       | 52.0                                                  |
| Max. sobna temperatura [°C]  | 60                                                    |
| Max. temperatura medija [°C] | 60                                                    |
| A [mm]                       | 99.7                                                  |
| B [mm]                       | 104.0                                                 |
| Pretok [l/min]               | 16000                                                 |