

Datum: 30.04.2025



(slika je simbolična)

## Vrtljiva varnosta spojka I.D. 6, ISO 6150 C, Fi 10

Kategorija: [Swivel safety coupling DN 6, with hose stem](#)

Šifra: **141745RIE**

### Kratek opis

Swivel safety coupling I.D. 6, ISO 6150 C, Steel, Sleeve I.D. 10, two-stage, Operating pressure max. 25 bar, Temp. -20°C to 100°C

High quality, robust and long lifetime one-hand rotation secure coupling.

A secure connection is made by pushing in the plug-in nipple that clicks in audibly. Uncoupling is done by rotating the sleeve anti-clockwise. For this, the pending pressure in the coupling and line are vented, however the plug-in nipple is not completely released via a safety latch. The plug-in nipple can only be pulled out after a clockwise rotation of the sleeve.

This coupling meets ISO standard DIN EN ISO 4414, EN 983. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive, mining.

### Tehnične Specifikacije

|                                |                                                                                        |
|--------------------------------|----------------------------------------------------------------------------------------|
| Min. temperaturno območje [°C] | -20                                                                                    |
| Delovni tlak                   | max. 25 bar / max. 16 bar when attaching / detaching at 6 bar and $\Delta_p = 0.5$ bar |
| Merjenje pretoka               | Galvanised steel                                                                       |
| Navojni kos                    | Steel, QPQ treated                                                                     |
| Ohišje                         | I.D. 10                                                                                |
| Povezava                       | Polyamide, red                                                                         |
| Rokav                          | Compressed air, gases                                                                  |
| Srednje                        | NBR                                                                                    |
| Tesnilo                        | Polyphenylene sulfide (PPS)                                                            |
| Ventil                         | acc. ISO 6150 C                                                                        |
| Vtični profil                  | Stainless steel                                                                        |
| Vzmet                          | 6                                                                                      |
| DN                             | 22                                                                                     |
| a/f [mm]                       | 70.0                                                                                   |
| Dolžina [mm]                   | 100                                                                                    |
| Max. temperaturno območje [°C] | 630 l/min (air)                                                                        |
| Pretok                         |                                                                                        |