

Datum: 30.04.2025

Davčna št.: SI 56119488

Telefon: 01 500 14 42

E-mail: info@podjetje-trg.si

WWW: www.karchertest.staging.digitalist.si



(slika je simbolična)

Vtični-L fitting Metallice vrt., G 3/8 , cev Ø 12

Kategorija: [Male elbow, swivel type, parallel ET with O-ring](#)

Šifra: **108906RIE**

Kratek opis

Push-in L-fitting »metallica«, rotating, G 3/8 o., for hose exterior Ø 12, Working pressure -0.98 to 16 bar, nickel-plated brass

All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. delovni tlak [bar]	-0.98
Material	Nickel-plated brass
Navoj	G 3/8
Priporočena cev	PA and PU
Rokav	Nickel-plated brass
Serijska	metallica
Vpenjalni obroč	Male elbow, swivel type, parallel male thread with O-ring (FPM)
Za cevi O.D. [mm]	12
Max. delovni tlak [bar]	16
a/f [mm]	20
L2 [mm]	28.5
L1 [mm]	29.0
Max. delovna temperatura [°C]	150