

Datum: 29.04.2025



(slika je simbolična)

Zad.splakovalni filter z regul.jem tlaka, preizk. na DVGW, R 1

Kategorija: [Back-flushing filters with pressure regulator](#)

Šifra: **101424RIE**

Kratek opis

Back flush filter with pressure regulator, for potable water, DVGW tested, incl. pressure gauge, 90 µm to 110 µm, R 1 Combined station for filtering and regulating the pressure of drinking and domestic water in addition to well, process and cooling water for once-through cooling systems, consisting of a diaphragm pressure regulator with a pressure-reduced single-seated valve and a back-flushing filter.

The filter candle must be cleaned manually at regular intervals by back-flushing (flushing out dirt particles). Integrated back-flushing element with suction elements, back-flushing lever, wing lever for back-flushing element, hose connection for flushing water.

Tehnične Specifikacije

Cedilna košarica	Impact-resistant plastic
Merjenje pretoka	At pressure drop $\Delta_p =$ 0.2 bar
Navoj	R 1
Ohišje	Brass
Min. krmilno območje [bar]	2
Pretok KVS vrednost [m³/h]	3.5
Min. sobna temperatura [°C]	5
Min. temperatura vode [°C]	5
Max. krmilno območje [bar]	6
Max. vhodni tlak [bar]	16
DN	25
Max. temperatura vode [°C]	30
Max. sobna temperatura [°C]	40
A [mm]	79.7
Spodnja širina mrežice [µm]	110
B [mm]	213.0
C [mm]	392.8