

Datum: 29.04.2025



(slika je simbolična)

## Zaporni ventil na hitri priklop, 10 mm cevni priključek

Kategorija: [Quick-stop shut-off valves, chrome-plated brass](#)

Šifra: **103756RIE**

### Kratek opis

Quick connect blocking valve brass chrome plated,DIN 4817,10 mm pipe connec.,DN 7,max. 4 bar liquid gas/16bar non-corrosive gases

### Tehnične Specifikacije

|                               |                                                                   |
|-------------------------------|-------------------------------------------------------------------|
| Min. delovna temperatura [°C] | -20                                                               |
| Delovni tlak                  | max. 4 bar / 16 bar (depending on the medium)                     |
| DVGW odobritev                | DIN 4817-1:1981-04                                                |
| Kolo                          | Plastic                                                           |
| O-tesnilo                     | NBR quality (Perbunan-n), resistant to heating oil                |
| Ohišje                        | Chrome-plated brass Ms58                                          |
| Pretok                        | No information, this depends on the operating pressure and medium |
| Standardni navoj              | G thread acc. to DIN EN ISO 228-1                                 |
| Steblo                        | Brass Ms58                                                        |
| DN                            | 7                                                                 |
| Povezava                      | 10 mm pipe connection                                             |
| Max. delovna temperatura [°C] | 60                                                                |